

Technical Specifications Contour S 5.4

Sensitivity (2.83 V/1 m):	87 dB
IEC Long Term Power Handling:	< 350 watts
Impedance, Nominal:	4 ohms
Frequency Response: (+/- 3 dB)	30 Hz – 27 kHz
Internal Cabinet Volume:	69 litres
Bass Principle:	Bass reflex
Weight:	46.2 kg
Dimensions (W x H x D):	390 x 1460 x 410 mm
Crossover:	3 way
Crossover Frequencies:	800, 2000 Hz
Crossover Slope:	12 dB/oct; 6 dB/oct; 12 dB/oct
Recommended Placing:	Floor, freestanding

Remarks:	Tweeter:	<ul style="list-style-type: none">• Esotar• Magnetic fluid• 5 mm machined aluminium front, with high heat-dissipation, integrated in baffle• Pure aluminium wire voice coil• Neodymium magnet ring
	Midrange:	<ul style="list-style-type: none">• Die-cast chassis• 15 cm one-piece moulded MSP polypropylene cone• 38 mm pure aluminium wire voice coil, wound on aluminium former.
	Woofers:	<ul style="list-style-type: none">• Die-cast chassis• 20 cm one-piece moulded MSP polypropylene cone• 75 mm long throw pure aluminium wire voice coil, wound on Kapton® former
	Crossover:	<ul style="list-style-type: none">• Thick glass fibre reinforced PCB with extra copper thickness• Capacitors with low loss dielectricum• Zero compression resistors• Inductors wounded on "air cores"• The crossover is impedance corrected