

## Technical Specifications Contour S C

Sensitivity (2.83 V/1 m):	86 dB
IEC Long Term Power Handling:	150 watts
Impedance, Nominal:	4 ohms
Frequency Response: (+/- 3 dB)	65 Hz – 25 kHz
Internal Cabinet Volume:	25 litres
Bass Principle:	Bass reflex
Weight:	10.3 kg
Dimensions (W x H x D):	490 x 160 x 303 mm
Crossover:	2 way
Crossover Frequencies:	1400 Hz
Crossover Slope:	6 dB/octave
Recommended Placing:	Stand or shelf

Remarks:	Speaker:	<ul style="list-style-type: none"><li>• Centre speaker</li></ul>
	Tweeter:	<ul style="list-style-type: none"><li>• 28 mm soft dome</li><li>• Esotar</li><li>• Magnetic fluid</li><li>• Pure aluminium wire voice coil</li></ul>
	Woofers:	<ul style="list-style-type: none"><li>• Die-cast chassis</li><li>• 15 cm one-piece moulded MSP polypropylene cone</li><li>• 75 mm long throw pure aluminium wire voice coil, wound on aluminium former</li></ul>
	Crossover:	<ul style="list-style-type: none"><li>• Thick glass fibre reinforced PCB with increased copper thickness</li><li>• Capacitors with low loss dielectric for clearer sound</li><li>• Zero compression resistors for dynamic reproduction</li><li>• Inductors wound on "air cores"</li><li>• Impedance corrected crossover for ideal Amplifier interface</li></ul>