

## Technical Specifications Contour S CX

Sensitivity (2.83 V/1 m):	87 dB
IEC Long Term Power Handling:	> 300 watts
Impedance, Nominal:	4 ohms
Frequency Response: (+/- 3 dB)	46 Hz – 22 kHz
Internal Cabinet Volume:	25 litres
Bass Principle:	Bass reflex
Weight:	18.0 kg
Dimensions (W x H x D):	800 x 193 x 318 mm
Crossover:	2 way
Crossover Frequencies:	2300 Hz
Crossover Slope:	Woofer 6 dB/octave; Tweeter 6 dB/octave
Recommended Placing:	Centre channel stand- or base mounted

Remarks:	Speaker:	<ul style="list-style-type: none"><li>• Centre speaker</li></ul>
	Tweeter:	<ul style="list-style-type: none"><li>• 28 mm soft dome</li><li>• Esotar<sup>2</sup></li><li>• Magnetic fluid</li><li>• 4 mm machined steel front, with high heat-dissipation, integrated in baffle</li><li>• Pure aluminium wire voice coil</li><li>• Integrated metal rear chamber, with built in acoustic-vent</li><li>• Large neodymium magnet rings</li><li>• Shielding magnet</li></ul>
	Woofers:	<ul style="list-style-type: none"><li>• 17 cm MSP cone</li><li>• 75 mm pure aluminium wire voice coil</li></ul>
	Crossover:	<ul style="list-style-type: none"><li>• Thick glass fibre reinforced PCB with increased copper thickness</li><li>• Capacitors with low loss dielectric for clearer sound</li><li>• Zero compression resistors for dynamic reproduction</li><li>• Impedance corrected crossover for ideal Amplifier interface</li></ul>