

Technical Specifications Evidence Temptation

Sensitivity (2.83 V/1 m):	90 dB
IEC Long Term Power Handling:	500 watts
Impedance, Nominal:	4 ohms
Frequency Response: (+/- 3 dB)	29 Hz – 25 kHz
Internal Cabinet Volume:	64 litres
Bass Principle:	Bass reflex
Weight:	113 kg
Dimensions (W x H x D):	210 / 390 x 1933 x 490 mm
Crossover:	3 (5) way
Crossover Frequencies:	(300 Hz), 500 Hz, 2300 (8000) Hz
Crossover Slope:	Woofers 6 dB/octave; Midranges 6 dB/octave; Tweeters 6 dB/octave
Recommended Placing:	Floor free standing

Remarks:	Tweeters:	<ul style="list-style-type: none">• 28 mm soft dome• Magnetic fluid• 40 mm aluminium-alloy front, with high heat-dissipation, integrated in baffle• Pure aluminium wire voice coil• Aluminium-alloy rear chamber with high heat dissipation• Very large neodymium magnet rings
	Midranges:	<ul style="list-style-type: none">• 15 cm one-piece moulded MSP cone• 38 mm pure aluminium wire voice coil
	Woofers:	<ul style="list-style-type: none">• 17 cm one-piece moulded MSP cone• 75 mm long throw pure aluminium wire voice coil
	Crossover:	<ul style="list-style-type: none">• Exchangeable filter module• Separate ventilated chamber for filter module• Non-magnetic filter frame• Double thickness glass fibre reinforced PCB with extra copper thickness• All speaker units and the crossover are impedance corrected• Only air-core coils• Capacitors with low loss dielectricum• Zero compression resistors