

Product Information DM 3/7

The Dynaudio DM 3/7

High-performance 2-way floor-standing loudspeaker offering remarkable value-for-money

The DM 3/7 is one of the finest floor-standing loudspeaker offerings in its price range. This latest Dynaudio DM series model features two 6.7 inch (17 cm) MSP (magnesium silicate polymer) mid/bass drivers equipped with large 3 inch (75 mm) diameter aluminium voice coils and rigid, low-resonance die-cast aluminium driver baskets. In concert with a large internal cabinet volume and a very solid 1 inch (25mm) front baffle, these proprietary drivers provide the DM 3/7 with the foundation for a very powerful, dynamic bass performance.

The tweeter also features renowned Dynaudio innovations: A specially-coated 1.1 inch (28 mm) diameter textile dome, an ultra-lightweight aluminium voice coil, ferrofluid damping and a powerful magnet. With this technology, the DM 3/7 provides a detailed and clear, yet homogenous and smooth high frequency reproduction. High quality crossover components and a rigid cabinet construction add to the value of this loudspeaker.

The DM 3/7 is suited for a wide range of amplifiers as validated by its linear constant impedance, a sensitivity rating of 86 dB and 200 W minimum long-term power handling.

To facilitate the most cost effective solution, only two finishes are offered: either rosewood or black ash high-quality laminates. While making the DM 3/7 extremely robust and durable, the furniture-grade quality of the laminate provides an elegant, wood-like finish.

- The first floor-standing model in the entry-level Dynaudio DM series
- 2-way design with dual mid/bass drivers
- Two 6.7 inch mid/bass drivers featuring MSP cone and aluminium voice coil
- Low-resonance die-cast aluminium driver baskets
- 28 mm coated soft-dome tweeter
- Available in high-quality rosewood or black ash laminate finishes

Technical Specifications

Sensitivity	86 dB
Recommended Amp. Power	> 25 watts for small size rooms > 65 watts for medium size rooms > 125 watts for large size rooms
IEC Power Handling	> 200 watts
Impedance	4 ohms
Frequency Response (+/- 3 dB)	40 Hz – 23 kHz
Int. Cabinet volume	35 litres
Bass principle	2-way Bass Reflex
Crossover Frequency	1800 Hz
Crossover Slope	Woofer: 12 dB/oct Tweeter: 12 dB/oct
Weight	18 kg
Dimensions (W x H x D)	204 x 960 x 275 mm

